
Product data sheet

LUCAS IX (1-ARMED BEADED) 9.859.3162.16

LEIPZIGER LEUCHTEN









Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge - Pole for single-bracket luminaire: dia. 76 mm, please order separately inquire separately for pole to suit double-bracket luminaire Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure mercury vapour lamp				
Nominal lamp power	125 W			
Lamp flux	6800 lm			
Luminous efficacy	40 lm/W			
CCT	3400 K			
CRI	54			

LOR	809	%
ULOR	49	%
Total flux	5439 lr	r
Total power	137 V	1



1 x High pressure mercury vapour lamp						
Nominal lamp power	80 W	LOR	80%			
Lamp flux	4000 lm	ULOR	4%			
Luminous efficacy	36 lm/W	Total flux	3199 lm			
CCT	3400 K	Total power	89 W			
CRI	54					

Mounting mode

Pole top mounted

Shape and measurements

Height: 23.62 in Diameter: 22.44 in Electric

System power: 89-137 W

Protection

IP: 55