# Product data sheet

ALDO 2 FLOODLINGHTS AND COLUMN PROJECTORS ALD-30091-M-W40

LIGMAN










- Lamp LED - Colour 3000K and 4000K - Powder coated aluminium alloy housing - Adjustable stainless steel bracket - Two cable entries for through wiring - Bright and consistent distribution, with seamless treatment with continuous mounting - Constant voltage (CV) 24V - Remote driver is not included - DC24V input, DMX512 address with constant current control for RGBW products

### Light output 1 (integrated)



Lamp type
Nominal lamp power
Total flux
Luminous efficacy

LED	CCT
24 W	CRI
2126 lm	LOR
89 lm/W	Total power

4032 H
80
100%
24 W

#### Mounting mode

Standing / Bollard, Ceiling mounted

### Shape and measurements

Length: 39.37 in Width: 1.46 in Height: 2.36 in Weight: 1.6 kg

### Adjustability

Fixed

## Design

Color of housing: Black, White, Silver gray

# Glare protection

Glare protection: UGR < 19

#### Electric

System power: 24 W Voltage: 230 V AC Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: III

## Protection

IP: 65 IK: 08

Surface temperature: 40°C Designation labels: CE