



Product data sheet

ODESSA 2 CLUSTER COLUMN PROJECTORS
OD-21011-W-W40-A80131
LIGMAN




–High-power LED · Colour stability · Mac Adam < 3 · Life time : 50000 h · Colour temperature : 3000K and 4000K Adjustable column stylish projector cluster solution.Flexible project solutions in symmetrical cluster arrangements utilising the naturally beautiful and unique contemporary Odessa projector range.

Light output 1 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	36.8 W	CRI	91
Total flux	2343 lm	LOR	100%
Luminous efficacy	64 lm/W	Total power	36.8 W

Light output 2 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	36.8 W	CRI	91
Total flux	2343 lm	LOR	100%
Luminous efficacy	64 lm/W	Total power	36.8 W

Light output 3 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	36.8 W	CRI	91
Total flux	2343 lm	LOR	100%
Luminous efficacy	64 lm/W	Total power	36.8 W

Mounting mode

Standing / Bollard, Wall mounted

Shape and measurements

Height: 157.48 in

Diameter: 5.12 in

Weight: 9.1 kg

Adjustability

Free

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 110.4 W

Voltage: 230 V AC

Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

Protection

IP: 66

IK: 07

Surface temperature: 40°C