Product data sheet

LIGHT SNIPER ROUND


03.4655/HI PAR 51/35W/GX10/10°25°40° FLOS





FLOS 23

High performance luminaires for embedded installation for halogen lamps with dichroic reflector, metal halide reflector or LED lamps. They offer a high comfort due to the back visual position of light source. Body of the luminaire made of two bodies of injected aluminium. Round front ring made of steel sheet 1mm thick with white matt finish. It incorporates shielded cones made in zamak injection in three sets: black, matt gold and chrome. Fixed, tilt and wall-washers versions. Spreading lens made in opal tempered glass in halogen fixed and tilt versions. In wall-washer versions a distribution lens made of borosilicate is incorporated.

Light output 1







1 x Metal halide lamp			
Nominal lamp power	35 W	Socket	Gx10
Lamp flux	2100 lm	LOR	47%
Luminous efficacy	28 lm/W	Total flux	981 lm
ССТ	3000 K	Total power	35 W
CRI	84		
1 M. (11) P. L. L			
1 x Metal halide lamp			0.10
Nominal lamp power	35 W	Socket	Gx10
Lamp flux	2100 lm	LOR	42%
Luminous efficacy	25 lm/W	Total flux	890 lm
CCT	3000 K	Total power	35 W
CRI	84		
1 x Metal halide lamp			0.40
Nominal lamp power	35 W	Socket	Gx10
Lamp flux	2100 lm	LOR	46%
Luminous efficacy	28 lm/W	Total flux	968 lm
CCT	3000 K	Total power	35 W
CRI	84		

Mounting mode

Ceiling recessed

Electric System power: 35 W

Shape and measurements

Height: 6.50 in Diameter: 3.94 in

Adjustability

Fixed

Protection

IP: 23