



Product data sheet

ELL 18L60 BD
ELEMENT
DEXTRA




Element LED - 1800mm Suspended bi-directional luminaire, white powder coated steel body with low glare microprism diffuser. Can be continuous run. Options: E3 - Emergency control gear (594 lumens output) ST3 - Emergency Selftest AT3 - Emergency Autotest S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function)* H - High Frequency Dimming (Analogue 1-10v) R44 - Daylight regulating and Occupancy Sensor RAS - Reacta Air Wireless occupancy and daylight dimming B - Black Body GY - Grey Body Continuous Run options: ST - Start of Run TW - Through Wire ER - End of Run ELL COR TW - Element Adjustable Through Wire Corner ELL BLIND 1260 TW - Element LED Suspended Continuous Run, 1260mm, 6 pole through wire blind unit ELL BLIND 1500 TW - Element LED Suspended Continuous Run, 1500mm, 6 pole through wire blind unit ELL EC - Element LED End Cap (please specify one set per run of luminaires). ELL JOINER - Element LED Joining Kit (required to connect End of Run to Start of Run luminaires where new power feeds are required mid run) P414 - 3M Suspension Kit

Light output 1 (integrated)



Lamp type		CCT	4000 K
Nominal lamp power	19.3 W	CRI	80
Total flux	2512 lm	LOR	100%
Luminous efficacy	130 lm/W	ULOR	100%
		Total power	19.3 W

Light output 2 (integrated)



Lamp type		CCT	4000 K
Nominal lamp power	21.1 W	CRI	80
Total flux	2517 lm	LOR	100%
Luminous efficacy	119 lm/W	Total power	21.1 W

Mounting mode

Pendant

Electric

System power: 40.4 W
Ballast: ECG
Appliance Class: I

Shape and measurements

Length: 70.87 in

Width: 9.06 in

Height: 1.61 in

Adjustability

Fixed

Protection

IP: 20

Designation labels: CE