Product data sheet

REKTOR 1XLED GI 3000K MEDIUM WHITE STRUC-SMOKED BRONZE 12828066

MODULAR






1 v I ED



Guiding the way around your space Rektor, the surface-mounted spotlight by Modular, will guide the way around your space. The unique feature of the Rektor is that all the technical workings are concealed within the fixture. The innovative tilting technology allows you to rotate the bulb holder through 360°, as well as adjusting it upwards or downwards through 90°. All without a single wire being visible. This makes it a perfect example of accent lighting. Its extensive adjustability and metal colour accent on the housing make it a genuine must-have. Rektor is also handy for highlighting a wall or specific object. Designed in cooperation with Couvreur-Devos.

Light output 1



I X LED	
Nominal lamp power	16.25 W
Lamp flux	1434 lm
Luminous efficacy	65 lm/W
CCT	3000 F
CRI	90

-					
⊢	Δ	വ	r	10	

System power: 19 W

Information regarding emergency functions

LOR

Total flux Total power

Supplementary emergency lighting

Emergency sign: N/A

Protection

IP: 20

Mounting mode

Ceiling mounted

Shape and measurements

Length: 3.07 in Width: 9.72 in Height: 1.81 in Weight: 1.38 kg

Adjustability

Rotatable, Tiltable

86% 1233 lm

19 W