
Product data sheet

LUCAS X (WALL FITTING) 9.833.2152.15 LEIPZIGER LEUCHTEN



Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure sodium vapour lan	۱p
-------------------------------------	----

Nominal lamp power	50 W	LOR	84%
Lamp flux	3500 lm	Total flux	2932 lm
Luminous efficacy	47 lm/W	Total power	62 W
CCT	2000 K		
CRI	25		

	"ATT
R	
\times	
Y	

1	x Hiah	pressure so	dium var	our lamp
	Aringii	pressure so	uluilli vup	Journamp

5 1			
Nominal lamp power	70 W	LOR	84%
Lamp flux	5600 lm	Total flux	4691 lm
Luminous efficacy	57 lm/W	Total power	83 W
CCT	2000 K		
CRI	25		

Mounting mode	Electric
Wall mounted	System power: 62-83 W
Shape and measurements	Protection
Height: 22.44 in	IP: 55
Diameter: 22.44 in	