

Product data sheet

SANTOS QUADRAT
311718.0044.1
RZB



IP
20

Series: Santos Quadrat Type of Protection: IP 20 Protection Class: I Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Base: metal, white, powder-coated. Diffuser fastening: spring system. Diffuser: opal glass, domed, frosted. Decorative frame: metal. Available Colours: chrome Type of Installation: Ceiling mounting, Wall (surface) Dimensions: L 410, B 410, H 105 Lamp: LED Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Luminaire flux LED: 1300lm System power: 28W Beam Angle: 113° Number of fittings B10A: 9 Number of fittings B16A: 15 Number of fittings C10A: 15 Number of fittings C16A: 25 Inrush current: 20A Unified Glare Ratio: 19,8 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	28 W	CRI	80
Total flux	1300 lm	LOR	100%
Luminous efficacy	46 lm/W	ULOR	3%
		Total power	28 W

Mounting mode

Ceiling mounted

Electric

System power: 28 W

Shape and measurements

Length: 16.14 in

Width: 16.14 in

Height: 3.74 in

Protection

IP: 20

Adjustability

Fixed