

Product data sheet

LIGHT LINEAR DENVER 3 STREET AND AREA LUMINAIRES


DE-20024-T3-W40

LIGMAN




- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Die-cast aluminium housing and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear toughened glass - Maximum wind load resistance is 100 km/h - Surge protection 10kV

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	155 W	CRI	80
Total flux	15976 lm	LOR	100%
Luminous efficacy	103 lm/W	Total power	155 W

Light output 2 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	155 W	CRI	80
Total flux	15976 lm	LOR	100%
Luminous efficacy	103 lm/W	Total power	155 W

Mounting mode

Standing / Bollard, Pole top mounted

Shape and measurements

Length: 84.65 in

Width: 5.91 in

Height: 3.54 in

Weight: 37.5 kg

Adjustability

Fixed

Glare protection

Glare protection: UGR < 19

Electric

System power: 310 W

Voltage: 230 V AC

Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

Design

Color of housing: Black, White, Silver gray

Protection

IP: 65

IK: 08

Surface temperature: 40°C