


# Product data sheet

FLAT SLIM  
312133.004.1.191  
RZB




IP  
65

IK  
03

Series: Flat Slim Type of Protection: IP 65 Protection Class: I Voltage: 220 - 230 V / 50 - 60 Hz Slave luminaire (SL), bracket powder-coated diecast aluminium, cover secured by bayonet connection, cover glass opal , satin finish. Available Colours: silver, metallic Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 300, H 63 Lamp: LED Life time: 50000 h (L70/B10) Colour Temperature: 4000K Socket 1: Stecker Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 1600lm System power: 21W Beam Angle: 128° Number of fittings B10A: 77 Number of fittings B16A: 124 Number of fittings C10A: 77 Number of fittings C16A: 124 Inrush current: 0,22A Unified Glare Ratio: 21,1 EEC: A+ - A+A+

## Light output 1 (integrated)



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Lamp type          | LED     | CCT         | 4000 K |
| Nominal lamp power | 21 W    | CRI         | 80     |
| Total flux         | 1600 lm | LOR         | 100%   |
| Luminous efficacy  | 76 lm/W | ULOR        | 14%    |
|                    |         | Total power | 21 W   |

## Mounting mode

Wall mounted

## Electric

System power: 21 W

## Shape and measurements

Height: 2.48 in  
Diameter: 11.81 in

## Protection

IP: 65  
IK: 03

## Adjustability

Fixed