

# Product data sheet

VRT3 L120 HR  
VERTECO3  
DEXTRA




IP  
20



Verteco 3 - IP20 Industrial Luminaire with high rack optics. Steel body white powder coated paint finish and green polycarbonate end caps. Mounting to lighting trunking using standard 20mm brass bush and locknut assembly. Side entry panel mount with female power feed plug supplied. Options: E3 - Emergency control gear (1044 lumens output) ST3 - Emergency Selftest AT3 - Emergency Autotest R18H - Reacta 18, Daylight and Presence Detection Sensor, Narrow Lens R18W - Reacta 18, Daylight and Presence Detection Sensor, Wide Lens R18HRF - Reacta 18, Daylight and Presence Detection Sensor, Wireless Version, Narrow Lens R18WRF - Reacta 18, Daylight and Presence Detection Sensor, Wireless Version, Wide Lens

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	67.3 W	CRI	80
Total flux	11548 lm	LOR	100%
Luminous efficacy	172 lm/W	Total power	67.3 W

## Mounting mode

Ceiling mounted, Pendant

## Shape and measurements

Length: 40.08 in

Width: 8.46 in

Height: 4.53 in

## Adjustability

Fixed

## Electric

System power: 67.3 W

Ballast: ECG

## Protection

IP: 20

Designation labels: CE