



Product data sheet

SURFACE BULKHEAD 300 SENSOR 15W/3000K BK IP65
4058075375284
LEDVANCE



Robust wall and ceiling luminaire with IP65 protection and high-frequency sensor. Product features: High frequency sensor for daylight and motion detection. UV-stabilized polycarbonate (PC) housing, PC-diffuser. Impact resistance: IK10. Push wire terminal for tool-free connection. Through wiring possible. Type of protection: IP65. Luminous flux: up to 1,400 lm. High luminous efficacy: up to 95 lm/W. Lifetime (L70/B50): up to 50,000 h (at 25 °C). Ambient temperature in operation: -20...+40 °C. Product benefits: Multiple adjustments of sensor range, daylight detection and hold time. Suitable for use in dusty and damp locations thanks to high IP rating. Suitable for use in public areas thanks to high IK rating. Separate covers available for an aesthetic and functional product design. 5 years guarantee. Multiple mounting patterns for convenient installation. Energy savings of up to 50 % (compared to luminaires that use fluorescent lamps). Areas of application: Direct replacement for luminaires with fluorescent lamps. Corridors, stairways, entrance areas. Passages, underpasses. Public areas. Equipment / Accessories: Additional cover rings in different designs available. Mounting screws and dowels included.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	1360 W	CRI	80
Total flux	1400 lm	LOR	100%
Luminous efficacy	1 lm/W	ULOR	3%
		Total power	1360 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 13.19 in
Width: 12.60 in
Height: 2.83 in
Weight: 740 kg

Adjustability

Fixed

Design

Material impression: Plastic
Color of housing: Black

Electric

System power: 1360 W
Appliance Class: II

Protection

IP: 65
IK: 10
Designation labels: CE

Other operating numbers

Ambient temperature range: -4...104°F