Product data sheet

LSRS8B/LSRSWM8B LED 8" SHALLOW ROUND CYLINDERS LSR8B40D010 EC8B40935 8LBM0MW

ENERGY STAR® qualified, 5-year warranty, Integral or remote driver options

COOPER LIGHTING






IP 47

Mounting: high bay/low bay ceiling, wall, stem or aircraft cable, Spun aluminum housing; Spun aluminum reflectors, 5 color temperatures: 2700K, 3000K, 3500K, 4000K and 5000K CCT, CRI: 80, 90 or 97; D2W™ option from 3000K to 1850K, Lumens: 1,000-6,000; W2N Tunable White 2700K-6500K or 2000K-5000K, Colors: Matte Black, White, Bronze and Silver paint finishes, Standard 0-10V dimming down to 1%,

Light output 1 (integrated)



_amp type	
Nominal lamp power	40
Total flux	376
_uminous efficacy	92 l

LED	CCT	3500 K
40.9 W	CRI	90
3760 lm	LOR	100%
92 lm/W	Total power	40.9 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 0.39 in Diameter: 8.00 in

Adjustability

Fixed

Electric

System power: 40.9 W

Protection

IP: 47