

Product data sheet

GANDALF 25 STREET AND AREA LIGHTING LUMINAIRES


GA-90252-T3-W40

LIGMAN




- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear toughened glass - Surge protection 10 kV

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	53.3 W	CRI	80
Total flux	6549 lm	LOR	100%
Luminous efficacy	123 lm/W	Total power	53.3 W

Light output 2 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	53.3 W	CRI	80
Total flux	6549 lm	LOR	100%
Luminous efficacy	123 lm/W	Total power	53.3 W

Mounting mode

Wall mounted, Pole top mounted

Shape and measurements

Length: 47.56 in

Width: 12.60 in

Height: 4.72 in

Weight: 15.5 kg

Adjustability

Free

Glare protection

Glare protection: UGR < 19

Electric

System power: 106.6 W

Voltage: 230 V AC

Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

Design

Color of housing: Black, White, Silver gray

Protection

IP: 65

IK: 08

Surface temperature: 40°C