

# Product data sheet

COLOUR  
501042.002  
RZB



IP  
44

IK  
07

Series: Colour Type of Protection: IP 44 Protection Class: I Voltage: 220 - 240 V / 50 Hz Base and protective cage: plastic. Two cable inlets. Cover: textured glass, transparent. Protective cage fastening with screws. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 200, H 100 Lamp: LED Life time: 32000 h (L70/B50) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK07 (2 Joule) Luminaire flux LED: 460lm System power: 9W Beam Angle: 57°/18°/60°/54° Unified Glare Ratio: 21,6 EEC: A+

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	9 W	CRI	80
Total flux	460 lm	LOR	100%
Luminous efficacy	51 lm/W	Total power	9 W

## Mounting mode

Wall mounted

## Shape and measurements

Height: 3.74 in  
Diameter: 7.87 in

## Adjustability

Fixed

## Electric

System power: 9 W

## Protection

IP: 44  
IK: 07