Product data sheet


LOTTO POST TOP LUMINAIRES
LO-20616-W40
LIGMAN



IP 55 IK 08

- Lamp COB - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Life time L90B10 Ta 25° 50,700 - Life time L80B10 Ta 50° > 63,500 - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Mat finishing aluminium reflector - Clear polycarbonate diffuser

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	41.2 W	CRI	80
Total flux	1162 lm	LOR	100%
Luminous efficacy	28 lm/W	ULOR	21%
		Total power	41.2 W

Mounting mode

Standing / Bollard, Pole top mounted

Shape and measurements

Height: 20.39 in
Diameter: 23.62 in
Weight: 22 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 41.2 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 55
IK: 08
Surface temperature: 40°C