


Product data sheet

SKYGARDEN 1 NRO
F6410030
FLOS



Suspension luminaire providing diffused lighting. Hemispherical, cast plaster diffuser, painted white inside. Outer finish: rust, glossy black, glossy white or matte gold. Plaster diffuser support in die-cast aluminum alloy. Upper cable gland and blocking ring nut in black injection-molded PC. Shaped, adjustment screws. Transparent, injection-molded, upper and lower silicone shock absorbers. Lamp-holder and fixing support in PPS. Flashed and blown opal glass diffuser. Molded fixing ring nut in die-cast aluminum alloy with alodine plating. Frieze in photo-etched and mechanically drawn AISI 304 steel. Molded and galvanized steel ceiling attachment. Gray, injection-molded PA6 (Nylon) rose , 4000 mm steel wire (1.2mm diameter). FEP/SIL UV-stabilized transparent power cord length 4000 mm. Net weight 13.6 kg .

Light output 1



1 x Halogen low voltage lamp without reflector

Nominal lamp power	150 W	Socket	E27
Lamp flux	2500 lm	LOR	54%
Luminous efficacy	9 lm/W	Total flux	1344 lm
CCT	2821 K	Total power	150 W
CRI	99		

Mounting mode

Pendant

Shape and measurements

Length: 23.73 in
Width: 23.73 in
Height: 11.73 in

Adjustability

Fixed

Electric

System power: 150 W

Protection

IP: 20