
Product data sheet

LESS IS MORE 27 312179.0045.1

RZB








Series: LESS IS MORE 27 Recessed ceiling and wall luminaire with slim design. Housing: extruded aluminium profile, powder-coated. End cap aluminium powder-coated. High polish aluminium micro grid. Perfect for office areas (UGR < 19) and environments with computer screens in accordance with EN 12464-1. Suitable for recessed ceiling mounting, wall (recessed). External driver with connecting cable. Colour: silver, matt (approx. RAL 9006) Length: 1514 mm Width: 38 mm Height: 2 mm Cut-out length: 1506 mm Cut-out width: 30 mm Recess height: 45-60 mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 82 System power: 39 W Rated luminous flux: 3500 lm Luminous efficiency: 90 lm/W Control gear: Regulated power supply Protection class: II Type of protection: IP 20

Light output 1 (integrated)



| Lamp type | LED | CCT | 4000 K |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 39 W | CRI | 80 |
| Total flux | 3500 lm | LOR | 100% |
| Luminous efficacy | 90 lm/W | Total power | 39 W |

Mounting mode

Ceiling recessed

Shape and measurements

Length: 1.50 in Width: 59.61 in Height: 0.08 in

Adjustability

Fixed

Design

Material impression: Matt Color of housing: Black

Electric

System power: 39 W Ballast: ECG

Protection

IP: 20

Designation labels: CE

Other operating numbers

Ambient temperature range: -4...77°F