
Product data sheet

LUCAS IX (1-ARMED BEADED) 9.859.2036.16

LEIPZIGER LEUCHTEN






CRI




Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets -Available in any RAL or DB colour without surcharge - Pole for single-bracket luminaire: dia. 76 mm, please order separately inquire separately for pole to suit double-bracket luminaire Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



I x High pressure sodium vapour lamp			
Nominal lamp power	50 W		
Lamp flux	3500 lm		
Luminous efficacy	45 lm/W		
CCT	2000 K		

LOR	80%
ULOR	4%
Total flux	2799 lm
Total power	62 W



1 x High pressure sodium vapour lamp

• •			
Nominal lamp power	70 W	LOR	80%
Lamp flux	5600 lm	ULOR	4%
Luminous efficacy	54 lm/W	Total flux	4479 lm
CCT	2000 K	Total power	83 W
CRI	25		

25

Mounting mode

Pole top mounted

Height: 23.62 in Diameter: 22.44 in

Shape and measurements

Electric

System power: 62-83 W

Protection

IP: 55

Designation labels: CE, F