


Product data sheet

SOM L42
SOMNUM
DEXTRA




Somnum - 1000mm Bi-Directional wall mounted luminaire with individually switched 75% upwards light, 25% downwards light distribution. Complete with white powder painted aluminium body and polycarbonate diffusers. Options: S - Switch Dimming (double switched up/down) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function) C83 - CRI 80, 3000K Also available for downlight only on request where mixed colour temperatures are required.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	8.2 W	CRI	80
Total flux	675 lm	LOR	100%
Luminous efficacy	82 lm/W	Total power	8.2 W

Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	18.06 W	CRI	80
Total flux	2202 lm	LOR	100%
Luminous efficacy	122 lm/W	ULOR	100%
		Total power	18.06 W

Mounting mode

Wall mounted

Shape and measurements

Length: 36.77 in

Width: 3.27 in

Height: 6.73 in

Adjustability

Fixed

Electric

System power: 26.26 W

Ballast: ECG

Protection

IP: 30

Designation labels: CE