


# Product data sheet

POZZO SCALE DELTA PENDANT D-I D650 840  
56125-402  
FAGERHULT



Installation Top point suspension in ceiling cup, c/c 48 mm. Height adjustment is made via friction lock. The ceiling cup can be mounted on sloping ceilings with a gradient of up to 20 degrees. Connection For connection with 230v built-in LED driver. Snap-in terminal block 5x2.5 mm². 1-phase through-wiring possible. 1-phase through-wiring possible. Surface mounted mains cable possible 180°. The luminaire is equipped with 2.6 m (Ø 500, Ø 650) or 3.8 m (Ø 850) cable, 5 x 0.75 mm², between luminaire and ceiling cup. Design Metal housing with white (RAL 9016) structured finish. Louvre Opal – plate in opal acrylic (PMMA). Delta – microprism louvre in acrylic (PMMA.). Light Distribution Direct/indirect 65/35. Dimming DALI/Phase-pulse control as standard. Miscellaneous A cut-out in the ceiling cup is made using cutters 94248 for a surface mounted mains cable.

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	50 W	CRI	80
Total flux	6002 lm	LOR	100%
Luminous efficacy	120 lm/W	ULOR	37%
		Total power	50 W

## Mounting mode

Pendant

## Electric

System power: 50 W

## Shape and measurements

Length: 25.61 in

Width: 25.80 in

Height: 2.06 in

## Protection

IP: 20

## Adjustability

Height adjustable

## Design

Color of housing: White