


# Product data sheet

## MEGASTAGE PROJECTOR


S.1395N

SIMES



Version is available on request. SPOTLIGHT POLE MOUNTED MEGASTAGE ROUND SPOT POLE MOUNTED S.1395N 1 module COB 4000K 220-240Vac DIMMABLE DALI; DALI2; PUSH Rated module luminous flux: : 8750lm Rated luminaire luminous flux: : 6123lm Rated module power: : 57.3W Rated luminaire power: : 62W Luminaire efficacy: : 99lm/W Voltage (AC): : 220-240Vac Frequency (AC): : 50/60Hz Voltage (DC): : 176-280Vdc (No PUSH DIM) Dimmable: : DALI; DALI2; PUSH PUSH Synchronization: - Max 4 Luminaires, distance <15m; - Max 35 Luminaires, distance <300m with S.2490 accessory. Electrical insulation class: : II Protection class IP: : IP66 Mechanical resistance: : IK09 CE SPECIAL VERSION ON REQUEST: this Luminaires can be supplied with a surcharge in class III (without power supply). Requires working remote power supply in constant current at 1600mA V<sub>fmin</sub>=31.2Vdc V<sub>fmax</sub>=36.8Vdc. LUMINAIRE TYPE Pole mounted Projector. IP rating IP 66 MATERIAL CHARACTERISTICS Die-cast EN AB-47100 aluminium housing with high corrosion resistance. Stone wash surface treatment prior to painting process. A4 grade Stainless Steel screws with 2,5-3% molybdenum content which increases the resistance against corrosion. Silicone gaskets. Painting Process : 3 Step Process 1) Surface treatment with BONDERITE. A heavy metal free chemical surface treatment containing ceramic nano particles giving a cohesive, inorganic and highly dense protective coating. 2) PRE POLYMERIZATION a process of introducing an epoxy primer with excellent characteristics to the paint which also offers very high resistance to oxidation due to its Zinc content. 3) POLYMERIZATION a process with the application of polyester powder with high resistance against UV rays and harsh weather conditions. Resistance test protection for Marine applications for 1200h. Mechanical resistance IK 09 LIGHTING PERFORMANCE 99.98% pure aluminium reflectors, or with concentrating lenses: The sophisticated optics focuses the beam and makes the light comfortable by reducing the direct glare of the light source. Clear toughened glass. LOR -- INSTALLATION AND MAINTENANCE MICROSTAGE ROUND POLE MOUNTED can be installed on poles ø60mm and ø76mm. MINISTAGE and STAGE POLE MOUNTED can be installed on poles ø60mm, ø76mm, and ø102mm, MINISTAGE may also be installed on top a pole on poles with 60mm diameter. STAGE POLE MOUNTED can be installed on poles ø60mm, ø76mm, and ø102mm, may also be installed on top a pole on poles with 60mm diameter. MEGASTAGE POLE MOUNTED can be installed on poles ø102mm and ø120mm. The tempered front glass diffuser is fixed externally to the fitting through silicon resin, perfectly flush with the front ring. Water and dirt deposits that can disturb the lighting performance of the projector can easily flow away. WIRING Supply 6m cable section type H05RNf sealed with B component epoxy resin, wired internally protected by silicon sheaths. Isolation: CLASS II . Available colours: Aluminium grey (cod.14), Anthracite grey (cod.24). Weight: 8.51 Kg Glow Wire test: -- LED module included REGISTERED DESIGN MICROSTAGE BLADE OF LIGHT PATENTED, REGISTERED DESIGN This luminaire contains built-in LED modules. In case of damage or malfunction please contact the manufacturer to receive additional instructions on how to replace and relative spare parts to order. The LED modules cannot be handled in the luminaire by the end user. This product contains a light source of energy efficiency class: E. LED modules are engineered accordingly to the existing regulations of Lumen Maintenance (LM80) and Technical Memorandum (TM21), where uniformity and quality of the light is 70,000 hours referred to L80 B10 Ta 25 ° C (50,000 hours referable to L80 B10 Ta 40°C). Lifespan of the luminaire min. 50,000 hours at 40°C. Performance Ambient temperature T<sub>a</sub> 25°C. Operating ambient temperature range is from -20°C to +50°C. Storage temperature range from -20°C to +60°C. ELECTRONIC EQUIPMENT SENSITIVE TO OVERVOLTAGE. We recommend installing surge protection devices ?SPD? in the electrical system. Protection devices prevent the intensity of these phenomena?s, protecting the appliances from the risk of being damaged and extending the lifespan. Outdoor luminaires are subject to all types of permanent, temporary, or transient electrical disturbances. Such disturbances can create permanent damage or failure affecting its performance and durability. The surge protection device (supplied by SIMES) is utilized to limit the destructive effect of these phenomena. We suggest that each luminaire must be connected to one protection device at not more than 10m away. For correct coordination of the protections, a surge protection device must also be provided inside the electrical panel of the system (the selection of this device must be carried out from the electrical designer and is not supplied by SIMES).

Light output 1 (integrated)



Lamp type		CCT	3000 K
Nominal lamp power	62 W	CRI	90
Total flux	6123 lm	LOR	100%
Luminous efficacy	99 lm/W	Total power	62 W

Mounting mode

Wall mounted, Ceiling mounted, Floor mounted

Shape and measurements

Height: 6.69 in  
Diameter: 7.12 in

Adjustability

Rotatable

Design

Material impression: Aluminum, Glass  
Color of housing: Silver gray  
Designer: SIMES S.P.A.

Electric

System power: 62 W  
Appliance Class: I

Protection

IP: 66  
IK: 08  
Designation labels: CE