

# Product data sheet


VOLKMAR III (2-ARMED)  
9.870.0206.00  
LEIPZIGER LEUCHTEN



IP  
55


For medium light requirements, mounting heights from 3.00 - 4.00 m. - Excellent uniform illumination, optimal glare protection - Mirror lamellae for light guidance and glare limitation made of premium highest grade aluminium, burnished and anodized - Luminaire body made of aluminium/galvanized steel sheet - Impact-resistant clear polycarbonate attachment, UV-stabilized - Steel tubing galvanized and painted - Adapter jack connection -Available in any RAL or DB colour without surcharge -Order pole for single-bracket luminaire, dia. 60 mm, separately - Order pole for multi-bracket luminaire, dia. 76 mm,separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

## Light output 1



|                              |         |             |         |
|------------------------------|---------|-------------|---------|
| 1 x Compact fluorescent lamp |         |             |         |
| Nominal lamp power           | 42 W    | LOR         | 55%     |
| Lamp flux                    | 3200 lm | ULOR        | 15%     |
| Luminous efficacy            | 38 lm/W | Total flux  | 1748 lm |
| CCT                          | 2899 K  | Total power | 46 W    |
| CRI                          | 90      |             |         |

## Light output 2



|                              |         |             |         |
|------------------------------|---------|-------------|---------|
| 1 x Compact fluorescent lamp |         |             |         |
| Nominal lamp power           | 42 W    | LOR         | 55%     |
| Lamp flux                    | 3200 lm | ULOR        | 15%     |
| Luminous efficacy            | 38 lm/W | Total flux  | 1748 lm |
| CCT                          | 2899 K  | Total power | 46 W    |
| CRI                          | 90      |             |         |

## Mounting mode

Pole top mounted

## Electric

System power: 92 W

## Shape and measurements

Height: 28.35 in

Diameter: 16.14 in

## Protection

IP: 55