

# Product data sheet

NORA VI (W. SHIELD ON SIDE FACING BUILDING CLEAR ATTACHMENT)

9.776.2032.35


LEIPZIGER LEUCHTEN



IP  
55

For medium light requirements, mounting height 3.50 - 4.00 m. - Impact-resistant clear or beaded polycarbonate attachment, UV-stabilized - Special reflector of premium highest-grade aluminium, burnished and anodized, for excellent illumination and glare protection - Aluminium luminaire body, inside finished in white paint, outside painted in colour - Aluminium unit carrier, painted white - Adapter jack connection - Available in any RAL or DB colour without surcharge - Scope of delivery includes special steel post/wall-mounted bracket, painted -Order post dia. 60 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



### 1 x High pressure sodium vapour lamp

Nominal lamp power	70 W	LOR	85%
Lamp flux	5600 lm	Total flux	4779 lm
Luminous efficacy	58 lm/W	Total power	83 W
CCT	2000 K		
CRI	25		

## Mounting mode

Pole top mounted

## Electric

System power: 83 W

## Shape and measurements

Height: 11.81 in

Diameter: 21.26 in

## Protection

IP: 55