


Product data sheet

UNILED ISOSAFE DIMTOWARM MATT WHITE 6W LED 2000-2800K RA>95
5046904211
SG ARMATUREN



Attractive downlight for indoor and outdoor use. Mounted directly in concrete via the special blade spring system. Well integrated LED chip, dimmable via phase-dimming or DALI driver (not IsoSafe). Made of die-cast powder-coated aluminium with a 10-year corrosion warranty or brushed steel (only indoors), glass diffuser. 42-degree scattering angle via reflector. 35 mm in total height, Flexible hole dimensions Ø76–Ø83. Tool-free mounting in mounting box for direct 230 V with loopable quick clips and automatic strain relief. IP54, KL II Light distribution Direct Light technic LED (not exchangeable) 7.3W 2000-2800K Ra>95 SDCM 3 L80/B20 >50,000 hrs at Ta=25°C Control/Dimming Trailing edge dimming Protection Class II SELV IP54 Energy and approvals A++ CE Materials and finish Housing: Aluminium Colour: Matt white (RAL 9003) Optics: Glass Mounting/Connection Recessed, Indoor / Outdoor Screwless terminal block

Light output 1 (integrated)



Lamp type	LED	CCT	2800 K
Nominal lamp power	7.3 W	CRI	95
Total flux	560 lm	LOR	100%
Luminous efficacy	77 lm/W	Total power	7.3 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 3.70 in

Width: 3.70 in

Height: 1.49 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 7.3 W

Appliance Class: II

Protection

IP: 54