


Product data sheet

SIRIUS 600 - CC WALL WASHER
8031-B-2-688-XX
UNILAMP




A brand new linear light family features various mounting application types including In-ground walk over, wall mounted, wall recessed, suspension and even permanently submersion stage. SIRIUS utilized the latest LED technology from world renowned manufactures with the choices of multiple light distributions. It offered narrow beam, medium beam, wide beam, asymmetric wall washer, wash glazing, bi-symmetric and much more. Thanks to a screw-less, clear and clean-cut design SIRIUS can be installed in most application where a decent architectural expression is required. Diversity types of connecting accessory is available for this linear light family.

Light output 1




1 x LED			
Nominal lamp power	4.3 W	LOR	98%
Lamp flux	555 lm	ULOR	98%
Luminous efficacy	129 lm/W	Total flux	544 lm
CCT	4000 K	Total power	4.3 W
CRI	85		

Light output 2




1 x LED			
Nominal lamp power	4.5 W	LOR	98%
Lamp flux	143 lm	ULOR	98%
Luminous efficacy	32 lm/W	Total flux	140 lm
CCT	0 K	Total power	4.5 W
CRI	-50		

Light output 3



1 x LED			
Nominal lamp power	4.1 W	LOR	98%
Lamp flux	486 lm	ULOR	98%
Luminous efficacy	119 lm/W	Total flux	477 lm
CCT	8000 K	Total power	4.1 W
CRI	-23		

Light output 4



1 x LED			
Nominal lamp power	3.4 W	LOR	98%
Lamp flux	196 lm	ULOR	98%
Luminous efficacy	58 lm/W	Total flux	192 lm
CCT	0 K	Total power	3.4 W
CRI	-36		

Mounting mode

Wall mounted

Shape and measurements

Length: 2.16 in
Width: 15.88 in
Height: 1.57 in

Adjustability

Free

Electric

System power: 16.3 W
Appliance Class: III

Protection

IP: 67
IK: 07