

# Product data sheet


COMPASS  
03.3522/QT-12/100W/75W/50W/35W/29°  
FLOS



IP  
23


Luminaire for halogen and high-pressure discharge lamps. Injection-moulded aluminium reflector body with powder-coated finish. Lamp support with die-cast aluminium, black powder-coated heat dissipating element. Thermoplastic recessed ring and screening ring, die-cast aluminium, black powder-coated anti-glare ring. 4 mm. tempered glass cover. Stainless steel fixing brackets.

## Light output 1




### 1 x Halogen low voltage lamp without reflector

Nominal lamp power	35 W	Socket	Gy6.35
Lamp flux	600 lm	LOR	79%
Luminous efficacy	14 lm/W	Total flux	474 lm
CCT	3000 K	Total power	35 W
CRI	99		




### 1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gy6.35
Lamp flux	910 lm	LOR	79%
Luminous efficacy	14 lm/W	Total flux	718 lm
CCT	3000 K	Total power	50 W
CRI	99		



### 1 x Halogen low voltage lamp without reflector

Nominal lamp power	75 W	Socket	Gy6.35
Lamp flux	1450 lm	LOR	79%
Luminous efficacy	15 lm/W	Total flux	1145 lm
CCT	2756 K	Total power	75 W
CRI	99		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	100 W	Socket	Gy6.35
Lamp flux	2200 lm	LOR	79%
Luminous efficacy	17 lm/W	Total flux	1737 lm
CCT	3000 K	Total power	100 W
CRI	99		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 8.66 in  
Diameter: 5.98 in

Adjustability

Tiltable

Electric

System power: 35-100 W

Protection

IP: 23