


# Product data sheet

CANTO 2000 WHITE 1400LM 3000K RA>80 TRAILING EDGE DIMMING  
7021986418668  
SG ARMATUREN



Design: Svein Knudsen / Andrew Smith Attractive, round luminaire that can be mounted to both walls and ceilings, and both indoors and outdoors. Made of die-cast powder-coated aluminium. Flat diffuser made of UV-stabilised opal polycarbonate. Many variants with both sensors and wireless control, as well as various lumen packages. Corrosion-proof with 10-year warranty, IP65 and vandal-resistant rating IK10. Light distribution Direct Light technic LED 14W 3000K Ra>80 SDCM 3 L70/B50 >100,000 hrs Control/Dimming Trailing edge dimming Protection Class I IP65 IK10 Fire protection class: 850°C - 30s Materials and finish Housing: Aluminium Colour: White (RAL 9003) Optics: UV-stabilized polycarbonate Mounting/Connection Surface, Indoor / Outdoor Screwless terminal block

## Light output 1



1 x LED			
Nominal lamp power	14 W	LOR	100%
Lamp flux	1400 lm	Total flux	1400 lm
Luminous efficacy	100 lm/W	Total power	14 W
CCT	3000 K		
CRI	80		

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 12.97 in  
Width: 12.97 in  
Height: 4.20 in

## Adjustability

Fixed

## Design

Color of housing: White

## Electric

System power: 14 W  
Appliance Class: I

## Protection

IP: 65  
IK: 10