Product data sheet

LADOR 12 SURFACE EXTERIOR DOWNLIGHTS

LD-80031-W-W40


LIGMAN





- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Life time L90B10 Ta 25° 135,000, 300,000 - Life time L80B10 Ta 50° 310,000, > 500,000 - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 316 - High-efficiency PMMA lens - Durable silicone rubber gasket - Clear toughened glass - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	39.3 W	CRI	80
Total flux	3258 lm	LOR	100%
Luminous efficacy	83 lm/W	Total power	39.3 W

Mounting mode

Ceiling mounted, Wall mounted

Shape and measurements

Length: 5.71 in Width: 5.71 in Height: 5.43 in Weight: 2.9 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 39.3 W Voltage: 230 V AC Ballast: ECG Controller: Dimmable 1..10V, DALI Appliance Class: I

Protection

IP: 65 IK: 07 Surface temperature: 40°C