


# Product data sheet

NIKON 2 RECESSED EXTERIOR DOWNLIGHTS  
NI-80513-VN-W40  
LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Life time L90B10 Ta 25° > 60,500 - Life time L80B10 Ta 50° > 60,500 - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - 6 mm thick front ring is available in stainless steel or aluminium - Single cable entry - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear toughened glass - Include control gear for NIKON 5, NIKON 6 - Remote driver is included for NIKON 1, NIKON 2,NIKON 3, NIKON 4 - Remote IP box is included for NIKON 1, NIKON 2,NIKON 3, NIKON 4

## Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	10.9 W	CRI	80
Total flux	722 lm	LOR	100%
Luminous efficacy	66 lm/W	Total power	10.9 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 4.72 in  
Width: 4.72 in  
Height: 3.46 in  
Weight: 0.6 kg

## Adjustability

Fixed

## Design

Color of housing: Black, White, Silver gray

## Glare protection

Glare protection: UGR < 19

## Electric

System power: 10.9 W  
Voltage: 230 V AC  
Ballast: ECG  
Controller: Dimmable 1..10V, DALI  
Appliance Class: I

## Protection

IP: 65  
IK: 08  
Surface temperature: 40°C