

Product data sheet

FLAT POLYMERO
672056.002.5.89
RZB




IP
40

IK
03


Series: FLAT POLYMERO Decorative round surface-mounted luminaire. For escape route illumination. Base: metal, powder-coated. Diffuser made of non-yellowing plastic (PMMA), opal. Diffuser fastening: patented push system. Suitable for ceiling mounting, wall (surface). Driver integrated. For connection to the emergency power supply. With AC Control monitoring module for LUXIFAIR central battery units. Colour: white Diameter: 360mm Height: 100mm Weight: 1.34kg Operating mode: maintained power mode Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 80 System power: 15W Rated luminous flux: 1450lm Luminous flux, emergency: 1450lm System power, emergency: 15W Control gear: Regulated power supply Protection class: I Type of protection: IP40

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	15 W	CRI	80
Total flux	1450 lm	LOR	100%
Luminous efficacy	97 lm/W	ULOR	12%
		Total power	15 W

Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	15 W	CRI	80
Total flux	1450 lm	LOR	100%
Luminous efficacy	97 lm/W	ULOR	12%
		Total power	15 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 3.94 in
Diameter: 14.17 in

Electric

System power: 30 W

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Adjustability

Fixed

Protection

IP: 40

IK: 03