



Product data sheet

MACRON-FLAT WALL LIGHT
7507-0-3-711-XX
UNILAMP



Description Known for its versatility MACRON utilizes louvers for controlled illumination in bollard applications. It allows for a symmetrical light distribution. Operated with high power COB LED. The clear polycarbonate cover with internal glare suppression louvers improves lighting quality by limiting the upward light emission. Macron is generally installed in walkways, parks, commercial areas and open spaces. It provides general illumination for any architectural environ as well as being an eye-catching object. MACRON can be customized to required heights and an anchor unit for concrete foundation is available as an accessory. Spec • Designed, Manufactured and tested according to IEC 60598-1, IEC 60598-2-1 and VDE regulations. • LM6 Die Cast Aluminium and Extruded Aluminium body. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • Polycarbonate diffuser. • Post-cured silicone gasket. • High quality LED module and driver. • Anodized aluminium louver. • GFR PA6.6 Terminal block. • Weather proof TPE grommet. • Pre-wired with outdoor cable. • Installation work has to be carried on according to the enclosed product manual.

Light output 1



1 x Metal halide lamp			
Nominal lamp power	70 W	Socket	E27
Lamp flux	5900 lm	LOR	34%
Luminous efficacy	84 lm/W	ULOR	10%
CCT	3000 K	Total flux	2004 lm
CRI	84	Total power	83 W

Mounting mode

Wall mounted

Shape and measurements

Length: 9.84 in
Width: 6.89 in
Height: 15.04 in

Adjustability

Fixed

Electric

System power: 83 W
Appliance Class: I

Protection

IP: 54
IK: 08