

# Product data sheet


ML56 LED RECESSED DOWNLIGHTS 90 CRI - 5 & 6 INCH  
ML5606940-594SNB-30  
COOPER LIGHTING



IP  
47

ENERGY STAR® Certified. Learn more at [energystar.gov](http://energystar.gov), 600 Design Lumens (typical), 90 CRI, Available in 2700K, 3000K, 3500K and 4000K color temperatures, D2W option - LED warms from 3000K to 1850K, Retrofits existing 5" or 6" housings with screwbase adapter included, Use with Halo 5" & 6" LED new construction & remodel housings, 120V-277V UNV Integral, thermally protected electronic LED driver, Dimmable on 120V phase-control dimmers, Wet location shower listed with reflector and baffle trims, ML56 modules with downlight trims make housings AIR-TITE™ (ASTM E283)

## Light output 1 (integrated)



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Lamp type          | LED     | CCT         | 3000 K |
| Nominal lamp power | 9.43 W  | CRI         | 100    |
| Total flux         | 783 lm  | LOR         | 100%   |
| Luminous efficacy  | 83 lm/W | ULOR        | 2%     |
|                    |         | Total power | 9.43 W |

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 3.94 in  
Width: 3.94 in  
Height: 3.94 in

## Adjustability

Fixed

## Electric

System power: 9.43 W

## Protection

IP: 47