


# Product data sheet

CUBE DIMTOWARM BLACK 980LM 2000-2800K RA>95  
906233  
SG ARMATUREN



Attractive downlight for indoor or outdoor use under eaves, 30-degree 360-degree stepless gyro tilt. Mounted directly on ceiling or on known ceiling electrical boxes. Well integrated LED chip with DimToWarm 2800K–2000K via phase-dimming. Made of die-cast powder-coated aluminium, glass diffuser. 42-degree beam angle angle via reflector. Quick connection between luminaire body and ceiling mounting plate. Luminaire body is snapped into place and secured using two concealed internal screws. Light distribution Direct Light technic LED (not exchangeable) 14.8W 2000-2800K Ra>95 SDCM 3 L90/B10 >50,000 hrs at Ta=25°C Control/Dimming Trailing edge dimming Protection Class I IP21 Energy and approvals A++ CE Materials and finish Housing: Aluminium and stainless steel Colour: Black (RAL 9004) Optics: Glass Mounting/Connection Surface, Indoor / Outdoor Screwless terminal block

## Light output 1 (integrated)



Lamp type	LED	CCT	2800 K
Nominal lamp power	14.8 W	CRI	95
Total flux	980 lm	LOR	100%
Luminous efficacy	66 lm/W	Total power	14.8 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 9.19 in

Width: 5.30 in

Height: 2.56 in

## Adjustability

Tiltable

## Design

Color of housing: Black

## Electric

System power: 14.8 W

Appliance Class: I

## Protection

IP: 21