

Product data sheet

FLAT POLYMERO
311556.002.7.76
RZB




IP
40

IK
03

Series: Flat Polymero Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Base: metal, powder-coated. Diffuser fastening: push lock. Diffuser: plastic (PMMA), opal. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 620, H 160 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter, dimmable, DALI Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 3100lm System power: 28W Beam Angle: 116° Number of fittings B10A: 22 Number of fittings B16A: 40 Inrush current: 34A Unified Glare Ratio: 18,4 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	28 W	CRI	80
Total flux	3100 lm	LOR	100%
Luminous efficacy	111 lm/W	ULOR	11%
		Total power	28 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 6.30 in
Diameter: 24.41 in

Adjustability

Fixed

Electric

System power: 28 W

Protection

IP: 40
IK: 03