


Product data sheet

BAMBOO 3 BOLLARDS
BA-10613-O-W40
LIGMAN



· Lamp COB · CRI Ra > 80 · MacAdam Ellipse 3 SDCM · Colour 3000K and 4000K - Die-cast aluminium housing and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - One IP68 connector supplied with 0.2 m of 3x1.0 sqmm outdoor cable - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear or opal, impact-resistant, UV-stabilised polycarbonate diffuser - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	14.3 W	CRI	80
Total flux	360 lm	LOR	100%
Luminous efficacy	25 lm/W	ULOR	50%
		Total power	14.3 W

Mounting mode

Standing / Bollard

Shape and measurements

Height: 26.18 in
Diameter: 4.02 in
Weight: 2.5 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 14.3 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 08
Surface temperature: 40°C