Product data sheet

AMOS 2 RECESSED DOWNLIGHTS AM-80031-N-W40

LIGMAN










- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour Temperature 3000K, 4000K - Eco-friendly LED product for energy saving and visual consistency. - Modular design for easy maintenance with future proofing. - Propriety lens design for high LOR. - Reliable thermal management for long life and lumen maintenance. - Dimming options available. - Excellent CRI for actual colour reproduction. - White powder coated aluminium reflector - Die-cast aluminium / White or black coated - Die-cast aluminium heat sink / Excellent thermal Management.

Light output 1 (integrated)



Lamp type	LE
Nominal lamp power	18.7
Total flux	1674
Luminous efficacy	90 lm/

LED	CCT	4032 K
18.7 W	CRI	80
1674 lm	LOR	100%
90 lm/W	Total power	18.7 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 6.81 in Diameter: 5.71 in Weight: 0.95 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 18.7 W Voltage: 230 V AC Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

Protection

IP: 20

Surface temperature: 40°C Designation labels: CE