

Product data sheet

SUPRALUM
251047.002
RZB




IP
43

IK
03

Series: Supralum Type of Protection: IP 43, IP 44 Protection Class: I Voltage: 220 - 240 V / 50 Hz Base: die-cast aluminium, powder-coated. Diffuser fastening: spring system. Diffuser: hand-blown opal glass, satin finish. IP43 ceiling mounted, IP44 wall mounted. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 220, H 90 Lamp: LED Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 430lm System power: 9W Beam Angle: 123° Unified Glare Ratio: 17,7 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	9 W	CRI	80
Total flux	430 lm	LOR	100%
Luminous efficacy	48 lm/W	ULOR	23%
		Total power	9 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 3.54 in
Diameter: 8.66 in

Adjustability

Fixed

Electric

System power: 9 W

Protection

IP: 43
IK: 03