

Product data sheet

FLAT POLYMERO
311526.002.7.19
RZB




IP
40

IK
03

Series: Flat Polymero Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 620, H 160 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 2600lm System power: 24W Beam Angle: 116° Number of fittings B10A: 15 Number of fittings B16A: 25 Number of fittings C10A: 26 Number of fittings C16A: 42 Inrush current: 10A Unified Glare Ratio: 17,8 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	24 W	CRI	80
Total flux	2600 lm	LOR	100%
Luminous efficacy	108 lm/W	ULOR	11%
		Total power	24 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 6.30 in
Diameter: 24.41 in

Adjustability

Fixed

Electric

System power: 24 W

Protection

IP: 40
IK: 03