Product data sheet

SMART LOTIS 115 ADJUSTABLE LED GE 2700K FLOOD GOLD 12781346

MODULAR









Smart lighting family Smart Cake, Smart Lotis and Smart Kup form a new generation of spotlights which combine technical ingenuity with timeless design. This family's styling is based on our most popular designs. In concrete terms, the fittings consist of a module which can be combined with one of three trims to suit your requirements. The new spotlights can be combined with Smart Mask or Smart surface box to form the perfect solution for any interior. What you get is a LED module with a different finish.

Light output 1




| 1 x LED | |
|--------------------|---------|
| Nominal lamp power | 13.4 W |
| Lamp flux | 956 lm |
| Luminous efficacy | 64 lm/W |
| CCT | 2700 K |
| CRI | 90 |
| | |

| LOR | 90% |
|-------------|--------|
| Total flux | 861 lm |
| Total power | 13.4 W |
| | |



| I X LED | |
|--------------------|---------|
| Nominal lamp power | 6.2 W |
| Lamp flux | 554 lm |
| Luminous efficacy | 80 lm/W |
| CCT | 2700 k |
| CRI | 90 |
| | |

| LOR | 90% |
|-------------|--------|
| Total flux | 499 lm |
| Total power | 6.2 W |
| | |
| | |



| 1 x LED | | | |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 9.2 W | LOR | 90% |
| Lamp flux | 744 lm | Total flux | 670 lm |
| Luminous efficacy | 73 lm/W | Total power | 9.2 W |
| CCT | 2700 K | | |
| CRI | 90 | | |

Mounting mode

Ceiling recessed

Electric

System power: 6.2-13.4 W Appliance Class: II

Shape and measurements

Length: 4.53 in Width: 4.53 in Height: 0.20 in

Adjustability

Tiltable

Protection

IP: 20