

Product data sheet


KTRIBE F2 CRO/ALL.ARG
F6305004
FLOS



IP
20

Floor lamp providing diffused lighting. Base, rod support and diffuser support in die-cast, polished Zamak alloy. Galvanized P04 steel base cover. Injection-molded PC (polycarbonate) opal inner diffuser and support for the lamp-holder. Outer diffusers in plissé cloth, transparent PMMA (polymethylmethacrylate), silver or bronze on the inner surface, by vacuum aluminum coating. Injection-molded PC (polycarbonate) upper ring, completely transparent or transparent diffuser and silver diffuser) or transparent brown for the outer bronze diffuser. Resistive dimmer wired on cord for 0-100% light adjustment. FEP/PVC, UV-stabilized transparent power cord length 1500 mm. Net weight 6.7 kg.

Light output 1



1 x Halogen low voltage lamp without reflector

Nominal lamp power	150 W	Socket	E27
Lamp flux	2500 lm	LOR	16%
Luminous efficacy	3 lm/W	ULOR	8%
CCT	2821 K	Total flux	408 lm
CRI	99	Total power	150 W

Mounting mode

Standing / Bollard, Floor mounted

Shape and measurements

Length: 15.55 in
Width: 15.55 in
Height: 63.80 in

Adjustability

Fixed

Electric

System power: 150 W

Protection

IP: 20