


Product data sheet

HOME 601
312183.002.76
RZB



Series: Home 601 Type of Protection: IP 40 Protection Class: II Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Frame: white powder coated aluminium. Diffuser: plastic (PMMA) microprismatic, (suitable for use in environments with computer screens in accordance with EN 12464-1), diffuser and light guide made of non-yellowing PMMA, lateral light emission with LED, lamp (LED) included, external converter (height 32mm) included Available Colours: white Type of Installation: Recessed ceiling mounting Dimensions: L 622, B 622, Lamp: LED Life time: 50000 h Colour Temperature: 3000K Operating Mode Lamp 1: Converter, dimmable, DALI Safety Marks: F-mark Luminaire flux LED: 3450lm System power: 36W Beam Angle: 85°/82° Inrush current: 20,4A Unified Glare Ratio: 17,7 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	36 W	CRI	80
Total flux	3450 lm	LOR	100%
Luminous efficacy	96 lm/W	Total power	36 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 24.49 in
Width: 24.49 in
Height: 0.59 in

Adjustability

Fixed

Electric

System power: 36 W

Protection

IP: 40