


Product data sheet

ALU-KREIS
251043.003
RZB



Series: Alu-Kreis Type of Protection: IP 43, IP 44 Protection Class: I Voltage: 220 - 240 V / 50 Hz Base: die-cast aluminium, powder-coated.
Diffuser fastening: spring system. Diffuser: hand-blown opal glass, satin finish. IP43 ceiling mounted, IP44 wall mounted. Available Colours: jet black (RAL 9005) Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 280, H 110 Lamp: LED Colour Temperature: 4000K
Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK02 (0,20 Joule)
Luminaire flux LED: 1250lm System power: 27W Beam Angle: 143° Unified Glare Ratio: 20,3 EEC: A+

Light output 1 (integrated)



| | | | |
|--------------------|---------|-------------|--------|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 27 W | CRI | 80 |
| Total flux | 1250 lm | LOR | 100% |
| Luminous efficacy | 46 lm/W | ULOR | 24% |
| | | Total power | 27 W |

Mounting mode

Ceiling mounted

Shape and measurements

Height: 4.72 in
Diameter: 11.02 in

Adjustability

Fixed

Design

Color of housing: Black

Electric

System power: 27 W

Protection

IP: 43
IK: 02