

Product data sheet

MINIPLANO FULL GLASS


S.5434W

SIMES



INGROUND WALKOVER MINIPLANO COMFORT S.5434W 1 module LED 3000K 220-240Vac ON-OFF Rated module luminous flux:: 194lm
Rated luminaire luminous flux: : 35lm Rated module power: : 1.5W Rated luminaire power: : 3W Luminaire efficacy: : 12lm/W Voltage (AC): :
220-240Vac Frequency (AC): : 50/60Hz Voltage (DC): : 176-264Vdc Dimmable: : NOT DIMMABLE (ON-OFF) Electrical insulation class: : I
Protection class IP: : IP65 IP67 Mechanical resistance: : IK09 CE SPECIAL VERSION ON REQUEST: this Luminaires can be supplied with a
surcharge in class III (without power supply). Requires working remote power supply in constant current at 500mA $V_{fmin}=V_{dc}$ $V_{fmax}=V_{dc}$.
Example SIMES compatible power supplies (check the complete list of the drivers on the catalogue): Art. S.2438 POWER SUPPLY
230V/250mA-700mA 20W o 230Vac/24Vdc 16W 240Hz DALI DIMMABLE IN BOX IP67 Art. S.3426 POWER SUPPLY DALI MULTI-POWER
230V/250mA-700mA o 230V/24V 16W 240Hz IP20 NB: Use 1 Power Supply for each Luminaires LUMINAIRE TYPE Inground walk over fitting.
Recessing depth 135 mm. IP rating IP 65 IP67 MATERIAL CHARACTERISTICS "Copper Free" Aluminium die cast housing in EN AB-44100 with
high resistance against corrosion. Stone wash surface treatment prior to painting process. A4 grade Stainless Steel screws with 2,5-3%
molybdenum content which increases the resistance against corrosion. Pre treated Silicone Gaskets. Painting Process : 3 Step Process 1)
Surface treatment with BONDERITE. A heavy metal free chemical surface treatment containing ceramic nano particles giving a cohesive,
inorganic and highly dense protective coating. 2) PRE POLYMERIZATION a process of introducing an epoxy primer with excellent
characteristics to the paint which also offers very high resistance to oxidation due to its Zinc content. 3) POLYMERIZATION a process with the
application of polyester powder with high resistance against UV rays and harsh weather conditions. Resistance test protection for Marine
applications for 1200h. Mechanical resistance IK 09 Maximum load capacity 1000 Kg LIGHTING PERFORMANCE Toughened acid-etched
sodic calcic Weiss glass 6mm thick with a high transmission degree + 12% (compared to the standard glass). Lamp fixed position. LOR -- LOW
SURFACE TEMPERATURE The high transmission properties of the Weiss glass means that the optimum LOR is achieved allowing more light
to pass through the glass resulting in the luminaire absorbing less heat. Surface temperature of glass 37°C (Ta 25°C) Specific layout of internal
components allow for better heat dissipation therefore limiting the temperature generated inside the fitting. RECESSING BOX Polypropylene
recessing box with external edge in stainless steel grade AISI 316L with cable entry on all 2 sides also allows: 1) Easy wiring; 2) Cable
management for fast connector; 3) Easy access to the fitting for maintenance purposes. WIRING Supply 0.5m cable section type H07RNF
secured by cable gland PG 13.5 (Ø 6÷12 mm) and sealed with B component epoxy resin, wired internally protected by silicon sheaths. Fast
connector M20 (Ø 5÷14 mm) supplied as standard for single cable connection . Connector housed inside the recessing box . Front re-lamping
without removing the complete fitting . Isolation: CLASS I . Finishing : FULL-GLASS Weight: 1.14 Kg Glow Wire test: -- LED module included This
luminaire contains built-in LED modules. In case of damage or malfunction please contact the manufacturer to receive additional instructions
on how to replace and relative spare parts to order. The LED modules cannot be handled in the luminaire by the end user. This product contains
a light source of energy efficiency class: E. LED modules are engineered accordingly to the existing regulations of Lumen Maintenance (LM80)
and Technical Memorandum (TM21), where uniformity and quality of the light is 70,000 hours referred to L80 B10 Ta 25 ° C (50,000 hours
referable to L80 B10 Ta 40°C). Lifespan of the luminaire min. 50,000 hours at 40°C. Performance Ambient temperature Tq 25°C. Operating
ambient temperature range is from -20°C to +50°C. Storage temperature range from -20°C to +60°C. ELECTRONIC EQUIPMENT SENSITIVE TO
OVERVOLTAGE. We recommend installing surge protection devices ?SPD? in the electrical system. Protection devices prevent the intensity of
these phenomena's, protecting the appliances from the risk of being damaged and extending the lifespan. Outdoor luminaires are subject to
all types of permanent, temporary, or transient electrical disturbances. Such disturbances can create permanent damage or failure affecting
its performance and durability. The surge protection device (supplied by SIMES) is utilized to limit the destructive effect of these phenomena.
We suggest that each luminaire must be connected to one protection device at not more than 10m away. For correct coordination of the
protections, a surge protection device must also be provided inside the electrical panel of the system (the selection of this device must be
carried out from the electrical designer and is not supplied by SIMES).

Light output 1 (integrated)



Lamp type		CCT	3000 K
Nominal lamp power	3 W	CRI	91
Total flux	35 lm	LOR	100%
Luminous efficacy	12 lm/W	ULOR	100%
		Total power	3 W

Mounting mode

Floor recessed

Shape and measurements

Height: 0.20 in

Diameter: 5.47 in

Adjustability

Tiltable

Electric

System power: 3 W

Appliance Class: I

Protection

IP: 67

IK: 09