


Product data sheet

SIRIUS 1200 - CC GROUND RECESS
9067-K-2-688-01
UNILAMP




Description SIRIUS a brand new linear light family features various mounting application types including in-ground walk over, wall mounted, ceiling mounted, suspension and even permanently submersion stage. SIRIUS utilized the latest LED technology from world renowned manufactures with the choices of multiple light distributions. It offered narrow beam, medium beam, wide beam, asymmetric wall washer, wash glazing, bi-symmetric and much more. Thanks to a screw-less, clear and clean-cut design SIRIUS can be installed in most application where a decent architectural expression is required. Diversity types of connecting accessory is available for this linear light family.

Light output 1




1 x LED			
Nominal lamp power	8.6 W	LOR	100%
Lamp flux	340 lm	ULOR	100%
Luminous efficacy	40 lm/W	Total flux	340 lm
CCT	4000 K	Total power	8.6 W
CRI	85		

Light output 2




1 x LED			
Nominal lamp power	9 W	LOR	100%
Lamp flux	238 lm	ULOR	100%
Luminous efficacy	26 lm/W	Total flux	237 lm
CCT	0 K	Total power	9 W
CRI	-50		

Light output 3



1 x LED			
Nominal lamp power	8.2 W	LOR	100%
Lamp flux	701 lm	ULOR	100%
Luminous efficacy	85 lm/W	Total flux	700 lm
CCT	8000 K	Total power	8.2 W
CRI	-23		

Light output 4



1 x LED			
Nominal lamp power	6.8 W	LOR	100%
Lamp flux	340 lm	ULOR	100%
Luminous efficacy	50 lm/W	Total flux	340 lm
CCT	0 K	Total power	6.8 W
CRI	-36		

Mounting mode

Floor recessed

Shape and measurements

Length: 46.95 in
Width: 3.70 in
Height: 5.41 in

Adjustability

Fixed

Electric

System power: 32.6 W
Appliance Class: III

Protection

IP: 67
IK: 10