

Product data sheet


EVA II (W. SHIELD ON SIDE FACING BUILDING)
9.898.3062.25
LEIPZIGER LEUCHTEN



IP
55

For high light requirements, mounting height 4.00 - 5.00 m. - Impact-resistant clear polycarbonate attachment, UV-stabilized - Large aluminium reflector for max. light output, inside in special white paint - Mirror lamellae for light guidance and glare limitation made of premium highest grade aluminium, burnished and anodized - Unit carrier made of hot die cast aluminium, corrosion-resistant, outside painted in colour - All electrical components are arranged on a block - Adapter jack for connection -Available in any RAL or DB colour without surcharge - Please order pole dia. 60 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x High pressure mercury vapour lamp

| | | | |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 125 W | LOR | 48% |
| Lamp flux | 6800 lm | ULOR | 10% |
| Luminous efficacy | 24 lm/W | Total flux | 3273 lm |
| CCT | 3400 K | Total power | 137 W |
| CRI | 54 | | |

Mounting mode

Pole top mounted

Shape and measurements

Height: 17.72 in
Diameter: 15.75 in

Electric

System power: 137 W

Protection

IP: 55