


Product data sheet

MARVIK 6 WALL SURFACE LUMINAIRES
MV-30052-VW-VW-W40
LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Life time L90B10 Ta 25° 135,000, 300,000 - Life time L80B10 Ta 50° 310,000, > 500,000 - Die-cast aluminium housing and frame pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency optical reflector - Clear toughened glass - Integral control gear

Light outputs 1..2 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	20 W	CRI	80
Total flux	1561 lm	LOR	100%
Luminous efficacy	78 lm/W	Total power	20 W

Mounting mode

Wall mounted

Shape and measurements

Height: 9.45 in
Diameter: 7.68 in
Weight: 4.6 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 40 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 08
Surface temperature: 40°C