

# Product data sheet


DEFINE LED WALL MOUNT LUMINAIRE  
S122RDIW-S485D970U840-4F0-1E-UDD-F1  
COOPER LIGHTING



IP  
47

Wall Mount Slot family in 2", 3", 4" and 5" housing sizes, Specifiable to the nearest 1', Multiple lensing options: flush satin, drop, regressed and asymmetric, Multiple lumen packages, 0-10V dimming standard; DALI dimming available, 2700K, 3000K, 3500K, 4000K & 5000K correlated color temperatures, VividTune CCT tuning options from 3000K–5000K or 2700K-6500K, Integral Wavelinx and Stand-alone sensors available, Customizable in-wall, in-ceiling and wall-to-ceiling corners available, DLC listed configurations available

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	45.2 W	CRI	80
Total flux	5108 lm	LOR	100%
Luminous efficacy	113 lm/W	ULOR	66%
		Total power	45.2 W

## Mounting mode

Wall mounted

## Shape and measurements

Length: 48.00 in  
Width: 2.00 in  
Height: 0.39 in

## Adjustability

Fixed

## Electric

System power: 45.2 W

## Protection

IP: 47