


Product data sheet

MATRIX 1 SQUARE WALL LUMINAIRES
MT-31396-M-W40
LIGMAN



- Lamp COB - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Life time L90B10 Ta 25? > 55,400 - Life time L80B10 Ta 50? > 55,400 - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear, impact-resistant, toughened glass diffuser - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	21 W	CRI	80
Total flux	1201 lm	LOR	100%
Luminous efficacy	57 lm/W	ULOR	6%
		Total power	21 W

Mounting mode

Wall mounted

Shape and measurements

Length: 7.09 in
Width: 6.30 in
Height: 6.30 in
Weight: 2.1 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 21 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 07
Surface temperature: 40°C