


# Product data sheet

FLEX STRIP OPAL LIVERPOOL DYNAMIC WHITE  
L60P407  
PROLED (MBN GMBH)




The PROLED FLEX STRIPS OPAL are perfect for outline illumination or homogenous light lines (e.g. for fair or shop applications, ...). Due to their shallow design and the individually adaptable lengths the PROLED FLEX STRIPS OPAL offer a wide spectrum of application possibilities. - The colour temperature is continuously adjustable from 2700 K to 5700 K. - High flexibility – adaptable to round shapes. - Homogenous illumination (no visible light spots). - Installation with aluminum profile or special glue. - dimmable, adjustable colour temperature, controllable via DMX 512, DALI, KNX, 1-10 V, CASAMBI, RF by MULTI power supplies/controller

## Light output 1 (integrated)



Lamp type	LED	CCT	5700 K
Nominal lamp power	9.5 W	CRI	90
Total flux	280 lm	LOR	100%
Luminous efficacy	29 lm/W	Total power	9.5 W

## Light output 2 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	9.5 W	CRI	90
Total flux	280 lm	LOR	100%
Luminous efficacy	29 lm/W	Total power	9.5 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 39.37 in

Width: 0.39 in

Height: 0.71 in

## Adjustability

Fixed

## Electric

System power: 19 W

Color adjustable

Appliance Class: III

## Protection

IP: 54

## Other operating numbers

Ambient temperature range: 14...113°F